



The SVFT-UCP Universal Ceiling Panel is designed to mount the SurveyorVFT Camera Dome System In-Ceiling version. It is a 24 in. (610 mm) x 24 in. (610 mm) x 16 GA. (0.060 in., 1.5 mm) white color painted panel constructed of steel. It is suitable for indoor installations only. The SurveyorVFT is pushed up through the panel's cutout and secured with its built-in hardware. This panel can be used in any dropped ceiling installation where the standard 2 ft. x 2 ft. grid is installed.

**ASSOCIATED EQUIPMENT AND ACCESSORIES**

**Model SurveyorVFT Camera Dome System:** A compact, lightweight and intelligent security device comprised of a camera, pan/tilt drive, receiver and CPU-based electronics all in an attractive and covert enclosure. Refer to Product Specification V134.

**SVFT-UCP Universal Ceiling Panel for SurveyorVFT Camera Dome System**

- Convenient mounting for SurveyorVFT in-ceiling version
- Color coordinated finish for ceiling and camera dome system
- Provides ultimate SurveyorVFT support
- Indoor/outdoor application

**Contractors' Specification**

**TECHNICAL SPECIFICATIONS  
DIVISION 13 - SPECIAL CONSTRUCTION  
SECTION 137\_\_ - SECURITY CCTV SYSTEM**

**SECURITY SYSTEM**

**PART 2 - PRODUCTS**

**2.01 GENERAL**

- A. All equipment and materials used shall be standard components, regularly manufactured, regularly utilized in the manufacturer's system.
- B. All systems and components shall have been thoroughly tested and proven in actual use.
- C. All systems and components shall be provided with the availability of a toll free 24-hour technical support phone number from the manufacturer. The phone number shall allow for immediate technical assistance for either the dealer/installer or the end user at no charge.
- D. All systems and components shall be provided with an explicit manufacturer warranty.

**2.02 UNIVERSAL CEILING PANEL FOR CAMERA DOME**

- A. The universal ceiling panel shall be designed to mount an in-ceiling camera dome system.
- B. It shall be suitable for indoor installations only.
- C. The camera dome shall be pushed up through the panel's cutout and secured with its built-in hardware.
- D. This panel shall be used in any dropped ceiling installation where the standard 2 ft. x 2 ft. grid is installed.
- E. The ceiling panel shall have the following mechanical specifications:
  - 1. Dimensions: 23.75-in. x 23.75-in. x 16 GA (0.060 in.) (603 mm x 603 mm. x 1.5 mm).
  - 2. Construction: Steel
  - 3. Color: White.

The Universal Ceiling Panel shall be Vicon Industries Model SVFT-UCP.



# Technical Information

**MECHANICAL**

**Application:** Indoor, specifically designed for in-ceiling SurveyorVFT.

**Mounting Surface:** 24 in. (610 mm) x 24 in. (610 mm) dropped ceiling grid.

**Dimensions:** See Figure.  
Length (L): 23.75 in. (603 mm).  
Width (W): 23.75 in. (603 mm).

**Thickness:** 0.060 in. (1.5 mm).

**Weight:** 8.5 lb (3.9 kg).

**Construction:** Sheet steel.

**Finish/Color:** Painted white.

**Shipping Dimensions:** Length: 24.5 in. (622 mm).  
Width: 24.5 in. (622 mm).  
Height: 1.25 in. (31.75 mm).

**Shipping Weight:** 10 lb (4.5 kg).

**Shipping Volume:** 0.43 ft<sup>3</sup> (0.012 m<sup>3</sup>).

**ENVIRONMENTAL**

**Storage Temperature Range:** -40 to 150° F (-40 to 60° C).

**Storage Humidity Range:** 0 to 90% relative, noncondensing.

