



SVFT-URM-1 Outdoor Roof Mount for SurveyorVFT Camera Dome System

- **Designed specifically for roof-mounting of SurveyorVFT Camera Dome System**
- **Allows convenient cabling for ease of installation**
- **Easy serviceability**

The SVFT-URM-1 Roof Mount is designed specifically to allow the SurveyorVFT Camera Dome System to be mounted to a roof. The roof mount provides a sturdy installation capable of withstanding extreme weather conditions. It allows the equipment to be swiveled onto the roof for easy serviceability and adjustment. Cabling is conveniently routed through the mount.

ASSOCIATED EQUIPMENT AND ACCESSORIES

Model SurveyorVFT Camera Dome System: A compact high-speed dome unit with an integral receiver, pan/tilt drive and camera/lens module. The SurveyorVFT system is modular and can be outfitted for indoor and outdoor use, with a variety of mounting accessories, and for various camera/lens module types. Refer to Product Specification V134.

Technical Information

MECHANICAL

- Mounting Thread:** Standard 1-1/2 in. NPT-F pipe thread.
- Load Rating:** 50 lb (23 kg). Designed to support the SurveyorVFT Dome.
- Dimensions:** Height (H): 37.0 in. (940 mm). Width (W): 27.0 in. (686 mm). Mounting Plate: 17 in. sq. (432 mm).
- Weight:** 22.5 lb (10.2 kg).
- Construction:** Mount: aluminum pipe. Braces and supports: steel. Hardware: stainless steel.
- Finish:** White paint.
- Shipping Dimensions:** (H x W x D): 2.5 x 38 x 30 in. (63.5 x 965 x 762 mm).
- Shipping Weight:** 25 lb (11.3 kg).
- Shipping Volume:** 1.65 ft³ (0.05 m³).
- ENVIRONMENTAL**
- Wind:** Withstands winds up to 80 mph.
- Storage Temperature:** -40 to 150° F (-40 to 65° C).
- Storage Humidity:** 90% relative, noncondensing.

